



KINGREASE
卓 | 信 | 宏 | 泰

Lubricating Grease Product Manual

Multi-Purpose High Grade
Lithium Base Grease

Multi-Purpose High Grade Lithium Base Grease



Product Description

This product is refined mineral oil thickened by 12-hydroxy fatty lithium soap acid, with antioxidant and anti-rust additives etc., It is a high-efficiency, long-lifetime grease. It has excellent mechanical stability, rust resistance and anti-oxidation stability. It is not easy to dilute and lose in using.

Application

- Applicable for lubrication of medium scale heavy load car's hub bearings, chassis, pump, electrical machinery and other machinery friction parts.
- Applicable for lubrication of sliding and rolling bearings of various mechanical equipments and other frictional parts.
- Operation temperature range: -20°C – 120°C.

Technical Date Sheet

Item	NLGI		Test method
	2#	3#	
Color	 Red		Visual
Worked cone penetration, 0.1mm	274	233	GB/T 269
Drop point, °C	135	136	GB/T 4929
Steel Mesh Oil Separation (100°C, 24h),%	4.1	1.1	SH/T 0324
Corrosion(T2 Copper, 100°C, 24h)	Pass	Pass	GB/T 7326 (B Method)
Anti-corrosion property(52°C, 48h), Level	1	1	GB/T 5018
Temperate range	-20°C – 120°C		

Caution

- Storage and transportation process to prevent the mixing of water and impurities.
- Can not mix with other grease.
- Can not be heated before use.
- Used grease remaining smooth in the original package in order to prevent gas.



Qingdao Kingrease Energy Co., Ltd.

Room 2901, Block A, Zhongnan Jinshi International Plaza,
Huangdao District, Qingdao City, Shandong Province, China.

Tel | +86 (532) 8699 7611

Fax | +86 (532) 8699 7611

www.kingrease.com

© Qingdao Kingrease Energy Co., Ltd. All rights reserved.