



# Lubricating Grease Product Manual

Semi Fluid Extreme Pressure Pumpable  
Lithium Base Grease

---

## **Semi Fluid Extreme Pressure Pumpable Lithium Base Grease**



### **Product Description**

This product is refined mineral oil thickened by fatty lithium soap acid with high performance additives. Offers excellent water resistance, pumpability and anti-oxidation stability.

Better leakproofness, lower consumption and lower noise emission than general lubricating oil.

### **Application**

- Suitable for the centralized lubrication system of all kinds of equipment.
- Suitable for the lubrication of friction parts of concrete pump truck, reducer, gearbox, etc.
- Operation temperature range: -20°C – 120°C.

---

## Technical Data Sheet

Item	NLGI			Test method
	0#	00#	000#	
Color and Apperance	■ Yellow Semi-Fluid			Visual
Worked cone penetration, 0.1mm	368	414	460	GB/T 269
Drop point, °C	175	160	155	GB/T 4929
Anti-corrosion property (45 No. steel, 100 °C, 3h)	Pass	Pass	Pass	GB/T 5018
Temperate range	-20°C – 120°C			

### Caution

- Storage and transporation process to prevent the mixing of water and impurities.
- Can not mix with other grease.
- Can not be heated before use.
- Used grease remaining smooth in the original package in order to prevent gas.



## **Qingdao Kingrease Energy Co., Ltd.**

Room 2901, Block A, Zhongnan Jinshi International Plaza,  
Huangdao District, Qingdao City, Shandong Province, China.

Tel | +86 (532) 8699 7611

Fax | +86 (532) 8699 7611

[www.kingrease.com](http://www.kingrease.com)

© Qingdao Kingrease Energy Co., Ltd. All rights reserved.