



KINGREASE
卓 | 信 | 宏 | 泰

Lubricating Grease Product Manual

Special grease for picking
spindle of cotton picker

Special grease for picking spindle of cotton picker



Product Description



Specially designed for picking gear of cotton picking machine, using reasonable thickener, high-quality base oil and additives, suitable for the lubrication of picking gear of cotton picking machine in centralized grease supply mode Lubrication requirements.

Excellent low temperature flow and pumping performance, excellent lubrication, protection performance, excellent anti-wear performance and operability.

Application

- Suitable for the lubrication of spindle gears of imported and domestic cotton pickers.
- Operation temperature range: -30°C – 120°C.

Technical Data Sheet

| Item | Data | Test method |
|--|---|-------------|
| Color |  Green  White | Visual |
| Worked cone penetration, 0.1mm | 404 | GB/T 269 |
| Drop point, °C | Green: 195 / White: 207 | GB/T 4929 |
| Anti-corrosion property (45 No. steel, 100 °C, 3h) | Pass | GB/T 5018 |
| Temperate range | -30°C – 120°C | |

Caution

- Storage and transportation process to prevent the mixing of water and impurities.
- Can not mix with other grease.
- Can not be heated before use.
- Used grease remaining smooth in the original package in order to prevent gas.



Qingdao Kingrease Energy Co., Ltd.

Room 2901, Block A, Zhongnan Jinshi International Plaza,
Huangdao District, Qingdao City, Shandong Province, China.

Tel | +86 (532) 8699 7611

Fax | +86 (532) 8699 7611

www.kingrease.com

© Qingdao Kingrease Energy Co., Ltd. All rights reserved.